



# Line Interactive UPS

## PRO700SFC/SFCU



Super Fast Charging



True AVR



Wide Input Voltage



Overload Protection



Over Temperature Protection




Surge Protection



Early Shutdown Warning System



Universal Socket



The **PRO700SFC/SFCU is a single-phase input/ single-phase output Line-Interactive 650VA UPS** is a single-phase input/ single-phase output Line-Interactive UPS system with PROLiNK's latest Super-Fast Charging technology. This cutting-edge technology is able to recharge the battery back to 90% of its capacity within 2-4 hours, perfect for areas with intermittent power.

Advance Early Warning system immediately alerts you to an output overload, high temperature or low battery condition, giving you ample time to either correct the condition or shut down your system before battery time runs out.

Intelligent Battery Management system provides additional protection for battery overcharging or deep discharging, while maximizing battery performance, life and reliability through intelligent precision charging. In the event of over temperature and overload, the device will automatically shutdown to prevent any damage from occurring.

Lastly, this device is supported with a wide input voltage range. The unit also comes with universal sockets to provide better compatibility with a wider range of connected devices.


**PRO700SFC/SFCU** is an ideal solution for safe and stable backup power to home/ small office applications.

## Key Features

- Built-in super fast charger, battery can be recharged to 90% of its capacity within 2-4 hours
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function
- Optional USB communication port
- Optional HID Compliant USB (for PRO700SFCU)

### Legend:

1. Power AC Input
2. Backup Outlets
3. USB Port (Only for PRO700SFCU)



## Specifications

<b>Capacity</b>		650VA
<b>Input</b>	Voltage Range Frequency Phase	140 ~ 300VAC $\pm$ 5% 50Hz/60Hz (Auto-sensing) Single + GND
<b>Output</b>	Voltage Range Battery Mode Frequency Waveform  Transfer Time	230VAC +12% - 14% 230VAC $\pm$ 10% 50Hz $\pm$ 1% (Battery mode) Simulated sine wave (Battery mode) Sine wave (AC mode) 2ms typical
<b>Battery</b>	Type Backup Time Recharge Time	12V/8.2AH - 1pc 8 - 30 mins depending on load 2 - 4 hours recover to 90% capacity
<b>Protection/ Monitoring</b>	Short Circuit Protection Surge Protection Alarm Overload Protection  Intelligent Battery Management	Yes (Line mode & battery mode) Yes Audible & Visual Line mode : 100 - 120% 5 mins change to fault mode >120% change to fault mode immediately Battery mode : 100 - 120% 5 secs shutdown >120% shutdown immediately  Prevent overcharging of battery Protect battery and prolong battery life
<b>Interface</b>	USB Connector*	AC fault, battery low, shutdown UPS
<b>General</b>	Noise Level Temperature Humidity Power Factor Built-in AVR	<40dB 0 °C - 40 °C 0 - 90% Up to 0.7 TRUE Full AVR (3 steps)
<b>Physical</b>	Dimension (D x W x H) Weight	279 x 101 x 142 4.2kg