

- ❖ Micro Processor controller : 12V-2Ah
- ❖ Polycrystalline Solar Panel : 18V-20W
- ❖ Sealed Lead Acid battery : 12V-12Ah  
(full charge 8-10hrs per panel)
- ❖ DC Output Socket : 12V/1.0A-6pcs
- ❖ 5V/500ma USB output socket : 2pcs
- ❖ Load : LED light, USB fan, Mini Radio, MP3, Mobile, Charger, Including 4pcs of 12V-2W LED lighting set (Bulb+wiring +socket)
- ❖ Working Temperature : -20C +55C
- ❖ Working Time : 4pcs x 2W LED bulbs last 5-7 hours with battery full charge
- ❖ Including one set of USB Multi-Plug for 10 types of common mobile phones
- ❖ Note : 12V-2W LED bulb = 10W fluorescent tube
- ❖ 12V-3W LED bulb = 15W fluorescent tube  
(Life span for LED bulb about 5000 hours)
- ❖ Important : The panel wire is 10m and MUST be connected to SOLAR IN input ONLY
- ❖ Never drain the battery until finish. Always Keep the panel wire hooked to the SOLAR IN jack all the time
- ❖ LIFE span for the battery about 6-8 years if used according to our specification
- ❖ Panel Charging about 8 hours  
Important : This maintenance free equipment's life span about 25 to 40 years if only used according to our instruction except the battery and bulb.

**PioneerTech Solar Power Pvt Ltd  
(Inc. in Singapore)**

33 C/12, President Lodge Complex,  
Thanjai Salai, Thiruvavur. (Near Bustand)  
email : [sales@comteck.com.sg](mailto:sales@comteck.com.sg)  
Tel: 73 73 73 22 30

International Office in Singapore :

55, Siglap rd,  
B1-01 Siglap Centre  
Singapore 455871  
Tel : 938 415 38



## Mini 20W Solar Power Generator

Quality Products can never be  
Compared with Inferior Products



誰が私たちの高品質の製品に対抗することができますか？



Highest in the Whole World

